

43 Series Fittings


Seal Lok®

Use with 301, 301LT, 304, 341, 381, 421, 421HT, 421WC, 424, 431, 436, 451TC, 471, 471ST, 481, 601, 604, and 881 hoses.

1JC43 Female Seal-Lok® - Swivel

Straight - Short

- Note: Seal-Lok® torque table in Section G.
- Note: Seal-Lok® O-Rings are listed in Section F.
- Note: Fittings with an "SM" suffix have a metric hex.
- Note: When measuring overall length to the end of the nut, B & C must be used to calculate cut-off allowance.
- Note: "C" - Stainless Steel Fitting. Must be crimped with Karrykrimp 2, PHastkrimp, Superkrimp, or Parkrimp 2.



#	Thread			Hose		A		C		H	W	B	
	Thread			Hose		inch		mm		inch	inch	inch	
	Part Number	inch	mm	inch	mm	inch	mm	inch	mm	inch	inch	inch	mm
1JC43-4-4	1/4	9/16x18	-4	1/4	-4	1.63	41	0.32	8	9/16	11/16	0.89	23
1JC43-4-4C	1/4	9/16x18	-4	1/4	-4	1.63	41	0.32	8	9/16	11/16	0.89	23
1JC43-4-4-SM	1/4	9/16x18	-4	1/4	-4	1.63	41	0.32	8	17 mm	17 mm	0.89	23
1JC43-4-6+	1/4	9/16x18	-4	3/8	-6	1.90	48	0.32	8	11/16	11/16	0.87	22
1JC43-4-6C+	1/4	9/16x18	-4	3/8	-6	1.90	48	0.32	8	11/16	11/16	0.87	22
1JC43-6-4	3/8	11/16x16	-6	1/4	-4	1.65	42	0.32	8	11/16	13/16	0.92	23
1JC43-6-4C+	3/8	11/16x16	-6	1/4	-4	1.65	42	0.32	8	11/16	13/16	0.92	23
1JC43-6-4-SM	3/8	11/16x16	-6	1/4	-4	1.68	43	0.32	8	17 mm	22 mm	0.93	24
1JC43-6-5	3/8	11/16x16	-6	5/16	-5	1.76	45	0.32	8	11/16	13/16	1.01	26
1JC43-6-6	3/8	11/16x16	-6	3/8	-6	1.94	49	0.38	10	11/16	13/16	0.91	23
1JC43-6-6C	3/8	11/16x16	-6	3/8	-6	1.94	49	0.38	10	11/16	13/16	0.91	23
1JC43-6-6-SM	3/8	11/16x16	-6	3/8	-6	1.94	49	0.38	10	19 mm	22 mm	0.91	23
1JC43-6-8C+	3/8	11/16x16	-6	1/2	-8	2.16	55	0.38	10	13/16	13/16	0.90	23
1JC43-6-8-SM	3/8	11/16x16	-6	1/2	-8	2.20	56	0.38	10	22 mm	22 mm	0.90	23
1JC43-8-6	1/2	13/16x16	-8	3/8	-6	1.98	50	0.38	10	13/16	15/16	0.98	25
1JC43-8-6C+	1/2	13/16x16	-8	3/8	-6	1.98	50	0.38	10	13/16	15/16	0.98	25
1JC43-8-6-SM	1/2	13/16x16	-8	3/8	-6	1.98	50	0.43	11	19 mm	24 mm	0.98	25
1JC43-8-8	1/2	13/16x16	-8	1/2	-8	2.22	56	0.43	11	13/16	15/16	0.96	24
1JC43-8-8C	1/2	13/16x16	-8	1/2	-8	2.22	56	0.43	11	13/16	15/16	0.96	24
1JC43-8-8-SM	1/2	13/16x16	-8	1/2	-8	2.22	56	0.43	11	22 mm	24 mm	0.96	24
1JC43-8-10+	1/2	13/16x16	-8	5/8	-10	2.36	60	0.43	11	15/16	15/16	0.95	24
1JC43-8-12+	1/2	13/16x16	-8	3/4	-12	2.40	61	0.43	11	1	15/16	0.97	25
1JC43-10-8	5/8	1x14	-10	1/2	-8	2.30	58	0.43	11	15/16	1-1/8	1.05	27
1JC43-10-8-SM	5/8	1x14	-10	1/2	-8	2.30	58	0.43	11	24 mm	30 mm	1.05	27
1JC43-10-10	5/8	1x14	-10	5/8	-10	2.50	64	0.53	13	15/16	1-1/8	1.05	27
1JC43-10-10C	5/8	1x14	-10	5/8	-10	2.50	64	0.53	13	15/16	1-1/8	1.05	27
1JC43-10-10-SM	5/8	1x14	-10	5/8	-10	2.49	63	0.53	13	24 mm	36 mm	1.05	27
1JC43-10-12+	5/8	1x14	-10	3/4	-12	2.63	67	0.53	13	1-1/8	1-1/8	1.19	30
1JC43-12-8	3/4	1-3/16x12	-12	1/2	-8	2.48	63	0.55	14	1-1/8	1-3/8	1.22	31
1JC43-12-8-SM+	3/4	1-3/16x12	-12	1/2	-8	2.48	63	0.57	14	32 mm	36 mm	1.22	31
1JC43-12-10	3/4	1-3/16x12	-12	5/8	-10	2.65	67	0.53	13	1-1/8	1-3/8	1.24	31
1JC43-12-10-SM	3/4	1-3/16x12	-12	5/8	-10	2.65	67	0.53	13	32 mm	36 mm	1.24	31
1JC43-12-12	3/4	1-3/16x12	-12	3/4	-12	2.68	68	0.57	14	1-1/8	1-3/8	1.24	31
1JC43-12-12C	3/4	1-3/16x12	-12	3/4	-12	2.68	68	0.57	14	1-1/8	1-3/8	1.24	31
1JC43-12-12-SM	3/4	1-3/16x12	-12	3/4	-12	2.68	68	0.57	14	32 mm	36 mm	1.24	31
1JC43-12-16	3/4	1-3/16x12	-12	1	-16	2.99	76	0.57	14	1-5/16	1-3/8	1.34	34
1JC43-16-12	1	1-7/16x12	-16	3/4	-12	2.81	71	0.58	15	1-3/8	1-5/8	1.38	35
1JC43-16-12-SM+	1	1-7/16x12	-16	3/4	-12	2.83	72	0.58	15	36 mm	41 mm	1.39	35
1JC43-16-16	1	1-7/16x12	-16	1	-16	3.14	80	0.58	15	1-3/8	1-5/8	1.52	39
1JC43-16-16C	1	1-7/16x12	-16	1	-16	3.14	80	0.58	15	1-3/8	1-5/8	1.52	39
1JC43-16-16-SM+	1	1-7/16x12	-16	1	-16	3.14	80	0.58	15	36 mm	41 mm	1.52	39
1JC43-20-16-SM+	1-1/4	1-1/16x12	-20	1	-16	3.08	78	0.59	15	41 mm	50 mm	1.46	37
1JC43-20-20+	1-1/4	1-11/16x12	-20	1-1/4	-20	3.23	82	0.59	15	1-7/8	1-7/8	1.58	40
1JC43-20-20C	1-1/4	1-11/16x12	-20	1-1/4	-20	3.23	82	0.59	15	1-7/8	1-7/8	1.58	40
1JC43-20-20-SM+	1-1/4	1-11/16x12	-20	1-1/4	-20	3.27	83	0.59	15	50 mm	50 mm	1.58	40
1JC43-24-24C+	1-1/2	2x12	-24	1-1/2	-24	2.94	75	0.57	14	2	2-1/4	1.61	41

+ Non-standard

Fittings
43 Series
B