


43 Series Fittings

Seal Lok®

Use with 301, 301LT, 304, 341, 381, 421, 421HT, 421WC, 424, 431, 436, 451TC, 471, 471ST, 481, 601, 604, and 881 hoses.

1J943 Female Seal-Lok® - Swivel 90° Elbow - Short Drop



^ Must use Parkrimp 2 or Superkrimp and Die Part No. 83C-A20H.

Note: Seal-Lok® torque table in Section G.

Note: Seal-Lok® O-Rings are listed in Section F.

Note: Fittings with an "SM" suffix have metric hex.

Note: "C" - Stainless Steel Fitting. Must be crimped with Karrykrimp 2, PHastkrimp, Superkrimp, or Parkrimp 2.

# Part Number	Thread			Hose		A		E		W		B	
	inch	mm	inches	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm
1J943-4-4	1/4	9/16x18	-4	1/4	-4	2.21	56	0.83	21	11/16	1.46	37	
1J943-4-4C+	1/4	9/16x18	-4	1/4	-4	1.78	45	0.80	20	11/16	1.03	26	
1J943-4-4-SM+	1/4	9/16x18	-4	1/4	-4	1.78	45	0.83	21	17mm	1.03	26	
1J943-4-6	1/4	9/16x18	-4	3/8	-6	2.33	59	0.82	21	11/16	1.33	34	
1J943-6-4	3/8	11/16x16	-6	1/4	-4	2.18	55	0.91	23	13/16	1.43	36	
1J943-6-4-SM+	3/8	11/16x16	-6	1/4	-4	2.18	55	0.91	23	22 mm	1.43	36	
1J943-6-5	3/8	11/16x16	-6	5/16	-5	2.26	57	0.90	23	13/16	1.51	38	
1J943-6-6	3/8	11/16x16	-6	3/8	-6	2.21	56	0.91	23	13/16	1.18	30	
1J943-6-6-SM	3/8	11/16x16	-6	3/8	-6	2.21	56	0.91	23	22 mm	1.18	30	
1J943-6-8	3/8	11/16x16	-6	1/2	-8	2.53	64	0.90	23	13/16	1.28	33	
1J943-6-8-SM	3/8	11/16x16	-6	1/2	-8	2.53	64	0.90	23	22 mm	1.28	33	
1J943-8-4	1/2	13/16x16	-8	1/4	-4	2.29	58	1.15	29	15/16	1.54	39	
1J943-8-6	1/2	13/16x16	-8	3/8	-6	2.37	60	1.14	29	15/16	1.34	34	
1J943-8-6-SM+	1/2	13/16x16	-8	3/8	-6	2.37	60	1.14	29	24 mm	1.34	34	
1J943-8-8	1/2	13/16x16	-8	1/2	-8	2.59	66	1.14	29	15/16	1.33	34	
1J943-8-8C+	1/2	13/16x16	-8	1/2	-8	2.64	67	1.19	30	15/16	1.38	35	
1J943-8-8-SM	1/2	13/16x16	-8	1/2	-8	2.59	66	1.14	29	24 mm	1.33	34	
1J943-8-10	1/2	13/16x16	-8	5/8	-10	2.79	71	1.15	29	15/16	1.38	35	
1J943-10-8	5/8	1x14	-10	1/2	-8	2.74	70	1.26	32	1-1/8	1.48	38	
1J943-10-8-SM+	5/8	1x14	-10	1/2	-8	2.74	70	1.26	32	30mm	1.48	38	
1J943-10-10	5/8	1x14	-10	5/8	-10	2.97	75	1.26	32	1-1/8	1.53	39	
1J943-10-10C+	5/8	1x14	-10	5/8	-10	2.97	75	1.26	32	1-1/8	1.53	39	
1J943-10-10-SM	5/8	1x14	-10	5/8	-10	2.97	75	1.26	32	30 mm	1.53	39	
1J943-10-12	5/8	1x14	-10	3/4	-12	3.06	78	1.27	32	1-1/8	1.63	41	
1J943-10-12-SM+	5/8	1x14	-10	3/4	-12	3.06	78	1.27	32	30 mm	1.63	41	
1J943-12-8	3/4	1-13/16x12	-12	1/2	-8	2.91	74	1.88	48	1-3/8	1.65	42	
1J943-12-8C+	3/4	1-13/16x12	-12	1/2	-8	3.17	81	1.88	48	1-3/8	1.92	49	
1J943-12-10	3/4	1-3/16x12	-12	5/8	-10	3.49	89	1.89	48	1-3/8	2.05	52	
1J943-12-10-SM+	3/4	1-3/16x12	-12	5/8	-10	3.49	89	1.89	48	36mm	2.05	52	
1J943-12-12	3/4	1-3/16x12	-12	3/4	-12	3.49	89	1.89	48	1-3/8	2.05	52	
1J943-12-12C+	3/4	1-3/16x12	-12	3/4	-12	3.34	85	1.89	48	1-3/8	1.92	49	
1J943-12-12-SM+	3/4	1-3/16x12	-12	3/4	-12	3.49	89	1.89	48	36 mm	2.05	52	
1J943-12-16	3/4	1-3/16x12	-12	1	-16	3.95	100	1.88	48	1-3/8	2.36	60	
1J943-12-16-SM+	3/4	1-3/16x12	-12	1	-16	3.95	100	1.85	47	36 mm	2.33	59	
1J943-16-12	1	1-7/16x12	-16	3/4	-12	4.07	103	2.21	56	1-5/8	2.64	67	
1J943-16-12C+	1	1-7/16x12	-16	3/4	-12	4.03	102	2.21	56	1-5/8	2.61	66	
1J943-16-16	1	1-7/16x12	-16	1	-16	4.28	109	2.20	56	1-5/8	2.66	68	
1J943-16-16-SM+	1	1-7/16x12	-16	1	-16	4.29	111	2.21	24	41 mm	2.69	70	
1J943-16-20	1	1-7/16x12	-16	1-1/4	-20	4.54	115	2.21	56	1-5/8	2.89	73	
1J943-20-16	1-1/4	1-11/16x12	-20	1	-16	4.69	119	2.51	64	1-7/8	3.10	79	
1J943-20-16C+	1-1/4	1-11/16x12	-20	1	-16	4.69	119	2.51	64	1-7/8	3.10	79	
1J943-20-20	1-1/4	1-11/16x12	-20	1-1/4	-20	4.85	123	2.51	64	1-7/8	3.20	81	
1J943-20-20-SM+	1-1/4	1-11/16x12	-20	1-1/4	-20	4.84	123	2.51	64	50 mm	3.19	81	
1J943-24-20^	1-1/2	2x12	-24	1-1/4	-20	4.97	126	2.70	69	2-1/4	3.32	84	
1J943-24-24	1-1/2	2x12	-24	1-1/2	-24	5.46	139	2.70	69	2-1/4	4.14	105	
1J943-24-24C+	1-1/2	2x12	-24	1-1/2	-24	5.51	140	2.70	69	2-1/4	4.11	104	

+ Non-standard