



## 2B-WD

英管外螺纹胶垫密封 / 英管内螺纹  
BSP MALE CAPTIVE SEAL/BSP FEMALE

| 代号<br>PART NO. | 螺纹 THREAD  |            | 胶垫 CAPTIVE |  | 尺寸 DIMENSIONS |      |      |    |    |
|----------------|------------|------------|------------|--|---------------|------|------|----|----|
|                | E          | F          | E 端        |  | A             | B    | L    | S1 | S2 |
| 2B-02WD        | G1/8"X28   | G1/8"X28   | WD-B02     |  | 8             | 5.5  | 24.5 | 14 | 14 |
| 2B-04WD        | G1/4"X19   | G1/4"X19   | WD-B04     |  | 12            | 5.5  | 31   | 19 | 19 |
| 2B-06WD        | G3/8"X19   | G3/8"X19   | WD-B06     |  | 12            | 6.3  | 34.5 | 22 | 22 |
| 2B-08WD        | G1/2"X14   | G1/2"X14   | WD-B08     |  | 14            | 7.5  | 41   | 27 | 27 |
| 2B-12WD        | G3/4"X14   | G3/4"X14   | WD-B12     |  | 16            | 10.9 | 45   | 32 | 32 |
| 2B-16WD        | G1"X11     | G1"X11     | WD-B16     |  | 18            | 11.7 | 50   | 41 | 41 |
| 2B-20WD        | G1.1/4"X11 | G1.1/4"X11 | WD-B20     |  | 20            | 11   | 56.5 | 50 | 50 |
| 2B-24WD        | G1.1/2"X11 | G1.1/2"X11 | WD-B24     |  | 22            | 13   | 59   | 55 | 55 |

| Nominal Bore Dia. |       | Design Working Pressure |      | Proof Pressure |      | Over Pressure |       |
|-------------------|-------|-------------------------|------|----------------|------|---------------|-------|
| mm                | ins   | BAR                     | psi  | BAR            | psi  | BAR           | psi   |
| 5                 | 1/8   | 350                     | 5145 | 525            | 7718 | 1400          | 20580 |
| 6.3               | 1/4   | 450                     | 6500 | 675            | 9750 | 1520          | 22000 |
| 10                | 3/8   | 380                     | 5500 | 570            | 8250 | 1310          | 19000 |
| 12.5              | 1/2   | 310                     | 4500 | 465            | 6750 | 1100          | 16000 |
| 14.25             | 9/16  | 289                     | 4250 | 434            | 6375 | 964           | 14170 |
| 16                | 5/8   | 280                     | 4000 | 420            | 6000 | 850           | 12350 |
| 19                | 3/4   | 240                     | 3500 | 360            | 5250 | 750           | 11000 |
| 25                | 1     | 210                     | 3000 | 315            | 4500 | 675           | 9750  |
| 31.5              | 1-1/4 | 170                     | 2500 | 255            | 3750 | 530           | 7700  |
| 37.5              | 1-1/2 | 136                     | 2000 | 204            | 3000 | 404           | 5940  |
| 50                | 2     | 136                     | 2000 | 204            | 3000 | 404           | 5940  |
| 62.5              | 2-1/2 | 84                      | 1240 | 126            | 1860 | 245           | 3596  |
| 75                | 3     | 76                      | 1120 | 114            | 1680 | 216           | 3170  |

## 1404B

### BSP MALE x BSP FEMALE SWIVEL - STRAIGHT

Part No.

Size

BSP M

BSP F



**1404B-04-04**

**1404B-06-06**

**1404B-08-08**

**1404B-12-12**

1/4

3/8

1/2

3/4

1/4

3/8

1/2

3/4