



90° 弯美制JIC外螺纹74°外锥 / 英管外螺纹O形圈

90° ELBOW JIC MALE 74° CONE / BSP MALE O-RING

1JG9-OG

代号 PART NO.	螺纹 THREAD		O形圈 O-RING		尺寸 DIMENSIONS			
	E	F		F端	A	B	S1	S2
1JG9-04-02OG	7/16"X20	G1/8"X28		O011	24.5	26.2	11	14
1JG9-04-06OG	7/16"X20	G3/8"X19		O113	27.5	36.8	16	22
1JG9-04OG	7/16"X20	G1/4"X19		O111	26.6	31.3	14	19
1JG9-05-04OG	1/2"X20	G1/4"X19		O111	26.5	31.8	14	19
1JG9-05-06OG	1/2"X20	G3/8"X19		O113	27.5	35.8	16	22
1JG9-05-08OG	1/2"X20	G1/2"X14		O115	31.5	43.2	22	27
1JG9-06-04OG	9/16"X18	G1/4"X19		O111	26.9	31.3	14	19
1JG9-06-08OG	9/16"X18	G1/2"X14		O115	32.5	43.2	22	27
1JG9-06OG	9/16"X18	G3/8"X19		O113	28.5	35.8	16	22
1JG9-08-04OG	3/4"X16	G1/4"X19		O111	32	33.5	19	19
1JG9-08OG	3/4"X16	G1/2"X14		O115	34.8	43.2	22	27
1JG9-08-06OG	3/4"X16	G3/8"X19		O113	32	36.8	19	22
1JG9-08-12OG	3/4"X16	G3/4"X14		O119	37.9	49.3	27	32
1JG9-10-06OG	7/8"X14	G3/8"X19		O113	37.8	39.2	22	22
1JG9-10-08OG	7/8"X14	G1/2"X14		O115	37.8	43.2	22	27
1JG9-10-12OG	7/8"X14	G3/4"X14		O119	41	49.3	27	32
1JG9-12OG	1.1/16"X12	G3/4"X14		O119	44.2	49.3	27	32
1JG9-12-08OG	1.1/16"X12	G1/2"X14		O115	44.2	46.5	27	27
1JG9-12-16OG	1.1/16"X12	G1"X11		O217	48	53	33	41
1JG9-16OG	1.5/16"X12	G1"X11		O217	49	53	33	41
1JG9-16-12OG	1.5/16"X12	G3/4"X14		O119	49	53	33	32
1JG9-16-20OG	1.5/16"X12	G1.1/4"X11		O222	53.8	58	41	50
1JG9-20OG	1.5/8"X12	G1.1/4"X11		O222	55.5	58	41	50
1JG9-20-16OG	1.5/8"X12	G1"X11		O217	55.5	58	41	41
1JG9-24-16OG	1.7/8"X12	G1"X11		O217	62.5	63	48	41
1JG9-24-20OG	1.7/8"X12	G1.1/4"X11		O222	62.5	63	48	50
1JG9-24OG	1.7/8"X12	G1.1/2"X11		O224	62.5	63	48	55

Adapter Pressure Ratings

These pressures as listed should be used as a guide only and not as a Standard or Specification!

Nominal Bore Dia.		Design Working Pressure		Proof Pressure		Over Pressure	
mm	ins	BAR	psi	BAR	psi	BAR	psi
5	1/8	350	5145	525	7718	1400	20580
6.3	1/4	450	6500	675	9750	1520	22000
10	3/8	380	5500	570	8250	1310	19000
12.5	1/2	310	4500	465	6750	1100	16000
14.25	9/16	289	4250	434	6375	964	14170
16	5/8	280	4000	420	6000	850	12350
19	3/4	240	3500	360	5250	750	11000
25	1	210	3000	315	4500	675	9750
31.5	1-1/4	170	2500	255	3750	530	7700
37.5	1-1/2	136	2000	204	3000	404	5940
50	2	136	2000	204	3000	404	5940
62.5	2-1/2	84	1240	126	1860	245	3596
75	3	76	1120	114	1680	216	3170