

### Additional Data/Spec Sheet


LP Brass Adapter Fittings – NPT Male x NPT Female 45° Elbow

## 2214P

45° Street Elbow



| Part Number | Pipe Thread |
|-------------|-------------|
| 2214P-2-2   | 1/8         |
| 2214P-4-4   | 1/4         |
| 2214P-6-6   | 3/8         |
| 2214P-8-8   | 1/2         |



## 45° Street Elbow 2214P

| PART NO.    | PIPE THREAD | M   | N    | FLOW DIA. D |
|-------------|-------------|-----|------|-------------|
| 2214P-2-2   | 1/8         | .38 | .50  | .220        |
| 2214P-4-4   | 1/4         | .54 | .70  | .314        |
| 2214P-6-6   | 3/8         | .56 | .78  | .440        |
| 2214P-8-8   | 1/2         | .73 | 1.00 | .564        |
| 2214P-12-12 | 3/4         | .75 | 1.35 | .750        |

### Assembly Instructions

#### Elbow or Tee Fittings

1. Hand tighten external thread into internal thread
2. Tighten an additional 1 to 1 1/2 turns with a wrench
3. Tighten fitting, clockwise to align with tubing. (Never counter clockwise)

Note: To minimize the possibility of a leaking threaded joint after assembling Male to female pipe threads, neither end should be backed out (loosened) Once the assembly has been made.