

Additional Data/Spec Sheet

LP Brass Adapter Fittings - NPT Female x NPT Male x NPT Female Branch Tee


2224P

Male Branch Tee

| Part | Pipe | |
|----------|--------|--|
| Number | Thread | |
| 2224P-2 | 1/8 | |
| 2224P-4 | 1/4 | |
| 2224P-6 | 3/8 | |
| 2224P-8 | 1/2 | |
| 2224P-12 | 3/4 | |







Male Branch Tee 2224P

| PART NO. | PIPE THREAD | L | м | N | FLOW DIA.D |
|----------|----------------|------|------|------|---------------|
| 2224P-2 | 1/8 | 1.06 | .53 | .66 | .220 |
| 2224P-4 | 1/4 | 1.52 | .76 | .91 | .314 |
| 2224P-6 | 3/8 | 1.68 | .84 | .97 | .440 |
| 2224P-8 | 1/2 | 2.18 | 1.09 | 1.25 | .564 |
| 2224P-12 | 3/4 | 2.32 | 1.16 | 1.38 | .752 |

Assembly Instructions

Elbow or Tee Fittings

- 1. Hand tighten external thread into internal thread
- 2. Tighten an additional 1 to 1 1/2 turns with a wrench
- 3. Tighten fitting, clockwise to align with tubing. (Never counter clockwise)

Note: To minimize the possibility of a leaking threaded joint after assembling Male to female pipe threads, neither end should be backed out (loosened) Once the assembly has been made.

