

Additional Data/Spec Sheet

LP Brass Adapter Fittings – Compression 90° Elbow

165C-265C

Union Elbow


Ref. SAE 060201 BA



Part Number	Tube Size	Straight Thread
165C-2	1/8	5/16-24
165C-3	3/16	3/8-24
165C-4	1/4	7/16-24
265C-4	1/4	7/16-24
165C-5	5/16	1/2-24
165C-6	3/8	9/16-24
165C-7	7/16	5/3-24
165C-8	1/2	11/16-20
165C-10	5/8	13/16-18
165C-12	3/4	1-18

Union Elbow 165C-265C

REF. SAE 060201 BA



PART NO.	TUBE SIZE	STRAIGHT THREAD	L	M	FLOW DIA. D
165C-2	1/8	5/16-24	.82	.61	.094
165C-3	3/16	3/8-24	.87	.61	.125
165C-4	1/4	7/16-24	.88	.61	.188
265C-4	1/4	7/16-24	.84	.60	.188
165C-5	5/16	1/2-24	.95	.71	.250
165C-6	3/8	9/16-24	1.03	.74	.312
165C-7	7/16	5/3-24	1.16	.82	.312
165C-8	1/2	11/16-20	1.34	.93	.406
165C-10	5/8	13/16-18	1.48	1.05	.500
165C-12	3/4	1-18	1.65	1.17	.563

PRESSURE RANGE @73°F		
PSI	TUBE O.D. (IN.)	TUBE WALL (IN.)
400	1/8	.030
400	9/16	.030
300	1/4	.030
300	5/16	.032
200	3/8	.032
200	1/2	.032
150	5/8	.035
100	3/4	.035
75	7/8	.035
<p>1. PRESSURE RATING IS BASED ON USE WITH SOFT METAL TUBING @ 73° F.</p> <p>2. THERMOPLASTIC TUBES USING ACETAL SLEEVE 60PT AND BRASS INSERT 63PT HAVE PRESSURE RANGES UP TO THE TUBE'S RATED WORKING PRESSURE.</p>		