

Additional Data/Spec Sheet

LP Brass Adapter Fittings – NPT Male x NPT Female Reducing Socket

209P
Bushing

| Part Number | Pipe Thread 1 | Pipe Thread 2 |
|-------------|---------------|---------------|
| 209P-4-2 | 1/8 | 1/4 |
| 209P-6-2 | 1/8 | 3/8 |
| 209P-6-4 | 1/4 | 3/8 |
| 209P-8-2 | 1/8 | 1/2 |
| 209P-8-4 | 1/4 | 1/2 |
| 209P-8-6 | 3/8 | 1/2 |
| 209P-12-2 | 1/8 | 3/4 |
| 209P-12-4 | 1/4 | 3/4 |
| 209P-12-6 | 3/8 | 3/4 |
| 209P-12-8 | 1/2 | 3/4 |
| 209P-16-8 | 1/2 | 1 |
| 209P-16-12 | 3/4 | 1 |

209P Bushing



| Part No. | 1 Pipe Thread | 2 Pipe Thread | C Hex. | L | Flow Dia. D |
|------------|---------------------|---------------------|-----------|------|----------------|
| 209P-4-2 | 1/8 | 1/4 | 9/16 | 0.75 | 0.339 |
| 209P-6-2 | 1/8 | 3/8 | 11/16 | 0.75 | 0.339 |
| 209P-6-4 | 1/4 | 3/8 | 11/16 | 0.75 | 0.441 |
| 209P-8-2 | 1/8 | 1/2 | 7/8 | 1.00 | 0.339 |
| 209P-8-4 | 1/4 | 1/2 | 7/8 | 1.00 | 0.441 |
| 209P-8-6 | 3/8 | 1/2 | 7/8 | 1.00 | 0.571 |
| 209P-12-2 | 1/8 | 3/4 | 1-1/8 | 1.00 | 0.339 |
| 209P-12-4 | 1/4 | 3/4 | 1-1/8 | 1.00 | 0.441 |
| 209P-12-6 | 3/8 | 3/4 | 1-1/8 | 1.00 | 0.571 |
| 209P-12-8 | 1/2 | 3/4 | 1-1/8 | 1.00 | 0.703 |
| 209P-16-8 | 1/2 | 1 | 1-3/8 | 1.31 | 0.703 |
| 209P-16-12 | 3/4 | 1 | 1-3/8 | 1.31 | 0.906 |

Assembly Instructions

Straight Fittings

1. Hand tighten external thread into internal thread
2. Tighten an additional 2 turns with a wrench up to 1/2" male pipe thread.
3. Above 1/2" 1 1/2 to 2 1/2 turns.