

Additional Data/Spec Sheet

D801 Series – Industrial Hose – Low Pressure – Dynamische Push-Lock Hose – Grey

Economical option to Parker 801 Series



We only stock Grey

PUSH-LOK HOSE **SAE J 517 100 R6** **EN 854**

HOSE CONSTRUCTION

INNER TUBE

Hydraulic Oil Resistant
Synthetic Rubber

REINFORCEMENT

High Tensile Synthetic
Textile Braid

COVER

Oil, Abrasion, Ozone & Weather
Resistant Synthetic Rubber

TEMPERATURE RANGE

(MEDIUM) -40°C to +100°C

APPLICATION

Push-On compatible applications

SAFETY FACTOR

4:1



Fluidco Part Numbers	Hose Size		I.D.	O.D.	Working Press		Burst Press		Bend Rad	Weight
	mm	inch	mm	mm	bar	psi	bar	psi	mm	kg/m
D801-04 PL-HOSE-04G	6	1/4	6.4	12.2	20	290	80	1160	76	0.14
D801-05	8	5/16	7.9	14.1	20	290	80	1160	76	0.17
D801-06 PL-HOSE-06G	10	3/8	9.53	15.4	20	290	80	1160	76	0.20
D801-08 PL-HOSE-08G	12	1/2	12.7	18.9	20	290	80	1160	127	0.23
D801-10 PL-HOSE-10G	26	5/8	15.88	22.8	20	290	80	1160	150	0.32
D801-12 PL-HOSE-12G	19	3/4	19.0	26.0	20	290	80	1160	180	0.39