


### Additional Data/Spec Sheet

Pneumatic Air & Gas Quick Coupler – 10 Series – Tru-Flate Desing – Automotive Interchange – Manual Sleeve - Single Shut Off

#### Performance 10 Series (1/4", 3/8", 1/2" sizes)



#### 10 Series Specifications

Body Size	1/4	3/8	1/2
Rated Pressure (psi)	300		
Temperature Range (std seals)	-40° to +250° F		
Locking Device	4 balls	8 balls	8 balls
Vacuum Data (in. Hg.)	—		
Disconnected (coupler only)	Not Recommended		
Connected	27.4		

#### Nipples - Standard Hose Barb



Body Size	Part No. Steel	Hose I.D.	Length	Exposed Length**	Largest Diameter	Weight (lbs)
1/2	5F	1/2	2.36	1.60	0.66	0.11



www.fluidco.co.za *Make it Happen!*

**10 Series** Pneumatic Couplers are the original Tru-Flate design, commonly referred to as the automotive interchange. 1/4" body size has a brass body, while standard 3/8" and 1/2" body sizes have all steel construction. Sleeve options include Sleeve-Lok and Grip-Ring sleeve .

**Features:**

- Integral sleeve guard resists accidental disconnection
- Tubular valve delivers high air flow with minimal pressure drop
- 3/8" and 1/2" size options include brass body with steel sleeve
- Standard seal is Nitrile
- Steel nipples are case hardened

**Applications include:**

- Air compressors
- Pneumatic tools
- Water
- Grease
- Paint