

Additional Data/Spec Sheet

Dowty Washers | Bonded Seal | BSP Thread | Carbon Steel | Buna Rubber Nitrile Seal (NBR)

TECHNICAL FEATURES:

- Carbon Steel AISI 1008-1010
- Seal: NBR 85 +/- 5 Sh A
- Surface Treatment: Zinc Plate (Cr3)
- Working Temperature: -30°C to +100°C

BSP Adaptor Bonded seals Steel Dowty Washers				DIMENSIONS mm			
Fluidco Part nr	DICSA Part nr	R1 BSP	(Bar) Burst Pressure	L	L1	L2	F
W-DW-02	T21002	1/8"	770	2	10.3	15.8	8.56
W-DW-04	T21004	1/4"	790	2	13.7	20.5	11.45
W-DW-06	T21006	3/8"	630	2	17.2	23.8	14.96
W-DW-08	T21008	1/2"	580	2	21.5	28.5	18.64
W-DW-10	T21010	5/8"	640	2	23.4	31.7	20.60
W-DW-12	T21012	3/4"	540	2	27	34.9	24.13
W-DW-16	T21016	1"	400	2.5	33.8	42.8	30.30
W-DW-20	T21020	1 1/4"	350	2.5	42.9	52.3	38.96
W-DW-24	T21024	1 1/2"	350	2.5	48.4	58.6	44.86
W-DW-32	T21032	2"	370	2.5	60.5	73	56.67

