




VSTI R-ED

BSPP Hollow Hex Plug

BSPP-ED

(for ISO 1179-1 / DIN 3852-2 Port)



END SIZE	D (mm)	L (mm)	S6 (mm)	Dynamic Pressure (x 1,000 PSI)		
1 BSPP				CF	71	MS
1/8 - 28	14	12.0	5	5.8	5.8	3.3
1/4 - 19	19	17.0	6	5.8	5.8	3.3
3/8 - 19	22	17.0	8	5.8	5.8	3.3
1/2 - 14	27	19.0	10	5.8	5.8	3.3
3/4 - 14	32	21.0	12	5.8	5.8	3.3
1 - 11	40	22.5	17	5.8	5.8	3.3
1 1/4 - 11	50	22.5	22	4.5	4.5	2.9
1 1/2 - 11	55	22.5	24	4.5	4.5	2.9

The main function of plugs for Ermeto DIN high pressure hydraulic fittings is the safe closure of ports in hydraulic systems. This broad range of fittings is available in steel with Cr(VI)-free surfaces and in stainless steel.

Features/ benefits:

- High corrosion resistance
- Stainless steel surface
- High pressure: The plugs have pressure ratings of up to 630 bar, so that the plugs can be used in a wide range of applications.