




Dimensional Drawings:

4F ORFS MALE O-RING PLUG HYDRAULIC PLUG ADAPTERS ORFS male dust protection plugs suppliers.



4F

美制ORFS外螺纹O型圈平面密封堵头
ORFS MALE O-RING PLUG

代号 PART NO.	螺纹 THREADE				尺寸 DIMENSIONS				
	E				A		S1		L
4F-04	U9/16"X18				12		19		18
4F-06	U11/16"X16				14		22		22
4F-08	U13/16"X16				15		27		24
4F-10	U1"X14				16.5		30		26
4F-12	U1.3/16"X12				17		36		27
4F-16	U1.7/16"X12				18.5		41		30
4F-20	U1.11/16"X12				19.5		50		36

O-Ring Face Seal (ORFS), SAE J1453 This connection is designed for leak-free use to 6000 PSI. The O-ring in the face of the straight thread male end seals against the flat face female seat and is mechanically held in place by a swivel nut.

Dash SizeInch SizeNominal Thread SizeMale Thread (O.D.)Female Thread (I.D.)

4	1/4"	9/16 -18	9/16" (.56)	.51"
6	3/8"	11/16 -16	11/16" (.68)	.63"
8	1/2"	13/16 -16	13/16" (.81)	.75"
10	3/8"	1 -14	1" (1.00)	.93"
12	3/4"	1 3/16 -12	1 3/16" (1.18)	1.10"
16	1"	1 7/16 -12	1 7/16" (1.44)	1.36"
20	1 1/4"	1 11/16 -12	1 11/16" (1.68)	1.60"
24	1 1/2"	2 -12	2" (2.00)	1.92"

Note: Since many factors influence the pressure at which a system will or will not perform satisfactory, values shown in this table should not be construed as guaranteed minimum.