


LP Brass Adapter Fittings – Compression Olive / Sleeve

## Sleeve 60C


REF. SAE 060115



| PART NO. | TUBE SIZE | A    | D    | L   |
|----------|-----------|------|------|-----|
| 60C-2    | 1/8       | .187 | .130 | .19 |
| 60C-3    | 3/16      | .266 | .192 | .22 |
| 60C-4    | 1/4       | .344 | .255 | .25 |
| 60C-5    | 5/16      | .406 | .318 | .25 |
| 60C-6    | 3/8       | .469 | .382 | .25 |
| 60C-8    | 1/2       | .594 | .507 | .38 |
| 60C-10   | 5/8       | .719 | .632 | .38 |

## Sleeve 60C

Ref. SAE 060115



| Part No. | Tube Size | A     | D    | L   |
|----------|-----------|-------|------|-----|
| 60C-2    | 1/8       | .187  | .130 | .19 |
| 60C-3    | 3/16      | .266  | .192 | .22 |
| 60C-4    | 1/4       | .344  | .255 | .25 |
| 60C-5    | 5/16      | .406  | .318 | .25 |
| 60C-6    | 3/8       | .469  | .382 | .25 |
| 60C-7    | 7/16      | .531  | .444 | .31 |
| 60C-8    | 1/2       | .594  | .507 | .38 |
| 60C-10   | 5/8       | .719  | .632 | .38 |
| 60C-12   | 3/4       | .875  | .758 | .44 |
| 60C-14   | 7/8       | 1.000 | .883 | .41 |

## 60C

### Sleeve

Ref. SAE 060115



| Part Number | Tube Size |
|-------------|-----------|
| 60C-2       | 1/8       |
| 60C-3       | 3/16      |
| 60C-4       | 1/4       |
| 60C-5       | 5/16      |
| 60C-6       | 3/8       |
| 60C-7       | 7/16      |
| 60C-8       | 1/2       |
| 60C-10      | 5/8       |
| 60C-12      | 3/4       |
| 60C-14      | 7/8       |

### Compression


1. Slide nut then sleeve onto tubing. The thread end of the nut must face out.
2. Insert tube and bottom on the fitting shoulder
3. Assemble nut to body and tighten "hand tight". Then wrench tighten the number of turns indicated in the table.



| FITTING SIZE | TUBE SIZE | TURNS REQUIRED TO SEAL FROM HAND-TIGHT |                                |
|--------------|-----------|----------------------------------------|--------------------------------|
|              |           | 60C WITH SOFT METAL TUBING             | 60PT WITH THERMOPLASTIC TUBING |
| 2            | 1/8       | 1-1/4                                  | —                              |
| 3            | 3/16      | 1-1/4                                  | —                              |
| 4            | 1/4       | 1-1/4                                  | 2                              |
| 5            | 5/16      | 1-1/4                                  | 2                              |
| 6            | 3/8       | 2-1/4                                  | 2                              |
| 8            | 1/2       | 2-1/4                                  | 2                              |
| 10           | 5/8       | 2-1/4                                  | 2                              |
| 12           | 3/4       | 2-1/4                                  | 2                              |
| 14           | 7/8       | 2-1/4                                  | —                              |

## Assembly Instructions

1. Slide nut then sleeve onto tubing. The thread end of the nut must face out.
2. Insert tube and bottom on the fitting shoulder
3. Assemble nut to body and tighten "hand tight". Then wrench tighten the number of turns indicated in the table.



| Fitting Size | Tube Size | Turns Required To Seal From Hand-Tight |                                |
|--------------|-----------|----------------------------------------|--------------------------------|
|              |           | 60c with Soft Metal Tubing             | 60pt with Thermoplastic Tubing |
| 2            | 1/8       | 1-1/4                                  | —                              |
| 3            | 3/16      | 1-1/4                                  | —                              |
| 4            | 1/4       | 1-1/4                                  | 2                              |
| 5            | 5/16      | 1-1/4                                  | 2                              |
| 6            | 3/8       | 2-1/4                                  | 2                              |
| 7            | 7/16      | 2-1/4                                  | —                              |
| 8            | 1/2       | 2-1/4                                  | 2                              |
| 10           | 5/8       | 2-1/4                                  | 2                              |
| 12           | 3/4       | 2-1/4                                  | 2                              |
| 14           | 7/8       | 2-1/4                                  | —                              |